

COMPRESSOR DEFINITION

Designation	NE K2150GK
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering number	959AA51

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-404A		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure R404A		
4.1 Evaporating temperature range	-40°C to -10°C	(-40°F to 14°F)	
5 Motor type	CSIR		
6 Starting torque	HST - Hight Starting Torque		
7 Expansion device	Capillary Tube or Expansion Valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C ambient temperature)	-	-	-
8.2 LBP (43°C ambient temperature)	-	-	-
8.3 HBP (32°C ambient temperature)	-	-	-
8.4 HBP (43°C ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	25.7	[kgf/cm ²] (365 psig)	/ °C - °F
9.2 Peak (gauge)	28.7	[kgf/cm ²] (408 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/2+	[hp]
2 Displacement	12.11	[cm ³] (0.739 cu.in)
2.1 Bore	19.000	
2.2 Stroke	10.000	
3 Lubricant charge (supplied)	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight(with oil charge)	11.55	[kg] (25.46 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single Phase)	
2 Starting device type	Current Relay	
2.1 Starting device		
3 Start capacitor	72-88(330)	[μF(VAC minimum)]
4 Run capacitor	-	[μF(VAC minimum)]
5 Motor protection (external)	T0634/G6	
6 Start winding resistance	30.40	[at 25°C (77°F)] +/- 8%
7 Run winding resistance	4.20	[at 25°C (77°F)] +/- 8%
8 LRA - Locked Rotor Amperage (50 Hz)	19.50	[A] - measured according to UL 984
9 FLA - Full Load Amperage LMBP (50 Hz)	-	[A] - measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - measured according to UL 984
11 Approval boards certification	IMQ	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Fan		Evaporating Temperature -23.3°C (-9.94°F) (Condensing Temperature 54.4°C (129.92°F))			
Cooling Capacity +/- 5%			Power Consumption +/- 5%	Current Consumption +/- 5%	Gas Flow Rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
2102	530	616	497	3.10	14.25	4.23	1.07	1.24

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE32 Fan		(Condensing Temperature 35°C (+95°F))					
Evaporating Temperature		Cooling Capacity +/- 5%			Power Consumption +/- 5%	Current Consumption +/- 5%	Gas Flow Rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	1066	269	312	303	2.73	7.17	3.51	0.88	1.03
-35	(-31)	1354	341	397	347	2.85	9.13	3.91	0.98	1.14
-30	(-22)	1733	437	508	392	2.97	11.72	4.42	1.12	1.30
-25	(-13)	2203	555	646	438	3.10	14.97	5.03	1.27	1.48
-20	(- 4)	2765	697	810	484	3.25	18.88	5.71	1.44	1.67
-15	(+ 5)	3418	861	1002	532	3.40	23.48	6.42	1.62	1.88
-10	(+14)	4163	1049	1220	582	3.57	28.80	7.15	1.80	2.09

TEST CONDITIONS: @220V50Hz			ASHRAE32 Fan		(Condensing Temperature 45°C (+113°F))					
Evaporating Temperature		Cooling Capacity +/- 5%			Power Consumption +/- 5%	Current Consumption +/- 5%	Gas Flow Rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	968	244	284	311	2.77	6.49	3.12	0.79	0.91
-35	(-31)	1245	314	365	359	2.88	8.38	3.47	0.87	1.02
-30	(-22)	1611	406	472	410	3.01	10.88	3.92	0.99	1.15
-25	(-13)	2065	520	605	464	3.17	14.00	4.44	1.12	1.30
-20	(- 4)	2607	657	764	521	3.34	17.77	5.00	1.26	1.47
-15	(+ 5)	3239	816	949	580	3.55	22.21	5.59	1.41	1.64
-10	(+14)	3959	998	1160	643	3.78	27.33	6.17	1.55	1.81

TEST CONDITIONS: @220V50Hz			ASHRAE32 Fan		(Condensing Temperature 55°C (+131°F))					
Evaporating Temperature		Cooling Capacity +/- 5%			Power Consumption +/- 5%	Current Consumption +/- 5%	Gas Flow Rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	886	223	260	314	2.82	5.93	2.82	0.71	0.83
-35	(-31)	1144	288	335	367	2.92	7.69	3.12	0.79	0.92
-30	(-22)	1488	375	436	424	3.06	10.03	3.51	0.88	1.03
-25	(-13)	1917	483	562	486	3.23	12.97	3.94	0.99	1.15
-20	(- 4)	2433	613	713	553	3.44	16.54	4.40	1.11	1.29
-15	(+ 5)	3034	765	889	624	3.69	20.76	4.87	1.23	1.43
-10	(+14)	3721	938	1090	700	3.98	25.64	5.30	1.34	1.55

F - EXTERNAL CHARACTERISTICS

1 Base Plate	European Standard
2 Tray Holder	No
3 Connectors	
3.1 SUCCTION	8.1 +0.10/+0.00 [mm] (0.319" +0.004"/+0.000")
3.1.1 Material	Copper
3.1.2 Shape	Slanted 42°
3.2 DISCHARGE	6.1 +0.10/+0.00 [mm] (0.240" +0.004"/+0.000")
3.2.1 Material	Copper
3.2.2 Shape	Straight
3.3 PROCESS	6.1 +0.10/+0.00 [mm] (0.240" +0.004"/+0.000")
3.3.1 Material	Copper
3.3.2 Shape	Slanted 42°
3.4 Oilcooler(Copper)	No [mm]
3.5 Connector sealing	Rubber Plugs